



# SOLVENT 694

## FAST DRYING CLEANING SOLVENT

### Product Description

A less aggressive, fast drying, flammable solvent blend for the removal of adhesive residues from finished parts and equipment that does not degrade EPS/Styrofoam and other plastic surfaces as more aggressive solvents can do.

### Benefits

- ✓ Does not degrade EPS and Styrofoam.
- ✓ Fast drying
- ✓ Softens adhesive residues permitting them to be removed as a semi-solid mass vs. needing to be completely dissolved.
- ✓ Less prone to damaging decorative surfaces than more aggressive solvents
- ✓ Contaminant free – leaves no oily residue when dry

### Suggested Uses

- Cleaning adhesive residues from finished parts.
- General cleaning of finished parts and equipment - marker pen, grease, pitch, etc.
- Detaching incorrectly positioned parts.

### Application

- **Do Not** use this, or any other product, to thin HELMITIN adhesives.
- To remove adhesive residue – Wipe with a cloth that is wet with solvent, but not dripping.
- **Do Not** flood surfaces with solvent as it will work into the seams, soften the adhesive and cause delamination. Keep the solvent exposure to edges and seams to a minimum to avoid this.
- Clean equipment immediately after use. Flush spray lines and spray guns until the discharged solvent runs clear. Brushes and rollers may be left to soak.
- To detach improperly positioned parts apply SOLVENT 694 directly to the glue-line. Keep the glue-line wet with solvent as the parts are gently pulled apart.

### Physical Properties

<b>Base:</b>	Solvent Blend
<b>Solids Content:</b>	0% (100% volatile)
<b>Viscosity:</b>	< 1 cP
<b>Specific Gravity:</b>	0.68
<b>Weight/Gal:</b>	5.7 lb
<b>Color:</b>	Clear
<b>VHAP:</b>	25% (wt/wt)
<b>VOC:</b>	680 g/L (5.68 lbs/gal); less water and exempt solvents

### Handling & Storage

- 12 month shelf life from date of manufacture
- Rotate stock to use the oldest material first
- **Does Not Freeze**
- Store below 35°C/95°F
- Keep containers tightly closed
- Avoid exposure of containers to direct sunlight

### Packaging

- 53 Gallon Drums, 5 Gallon Pails

### Warranty

*Because Seller has no control over methods of product application or conditions of use, its product is warranted only to be made of standard commercial grade materials and in conformance with Seller's published specifications, if any. Any recommendations for the use of the product are based on tests or experience believed to be reliable and are furnished without compensation, and Seller does not guarantee the applicability or the accuracy of this information or the suitability of its product in any given situation. Buyer must take its own tests to determine the suitability of Seller's product for Buyer's particular use and buyer assumes all risk and liability of use of Seller's product.*