

**SECTION 1: IDENTIFICATION****Product Identifier****Product Form:** Mixture**Product Name:** HELMISOLV 667**Intended Use of the Product****Use of the Substance/Mixture:** No use is specified.**Name, Address, and Telephone of the Responsible Party****Company**

Helmitin Inc.

99 Shorncliffe Rd

Toronto, Ontario, M8Z 5K7

877.823.2624

11110 Airport Road

Olive Branch, MS 38654

Phone: 877.823.2624

www.helmitin.com

**Emergency Telephone Number****Emergency Number** : CANUTEC 613-996-6666 / CHEMTREC 1-800-424-9300**SECTION 2: HAZARDS IDENTIFICATION****Classification of the Substance or Mixture****Classification (GHS-US)**

Flam. Liq. 2 H225


Skin Irrit. 2 H315

Eye Irrit. 2A H319

Asp Hzrd H304

STOT SE 3 H336

Full text of H-phrases: see section 16

**Label Elements****GHS-US Labeling****Hazard Pictograms (GHS-US)****Signal Word (GHS-US)**

: Danger

**Hazard Statements (GHS-US)**: H225 - Highly flammable liquid and vapor.  
H304 – May be fatal if swallowed or enters airway.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.**Precautionary Statements (GHS-US)**: P210 - Keep away from extremely high or low temperatures, ignition sources, and incompatible materials. - No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P261 - Avoid breathing vapors, mist, or spray.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

# HELMISOLV 667

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear respiratory protection, protective clothing, protective gloves, eye protection.  
P303+P361+P353 - IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 - Call a poison center or doctor if you feel unwell.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P370+P378 - In case of fire: Use Water, alcohol resistant foam, carbon dioxide (CO<sub>2</sub>), extinguishing powder, sand to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

### **Other Hazards**

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Flammable vapors can accumulate in head space of closed systems.

### **Unknown Acute Toxicity (GHS-US)**

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### **Mixture**

Name	Product Identifier	% (w/w)
Methyl acetate	(CAS No) 79-20-9	80 – 100
Heptane, branched, cyclic and linear	(CAS No) 426260-76-6	1 - 5
n-Heptane	(CAS No) 142-82-5	1 - 5

## SECTION 4: FIRST AID MEASURES

### **Description of First Aid Measures**

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

**Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

### **Most Important Symptoms and Effects Both Acute and Delayed**

**General:** Causes skin irritation. May cause drowsiness or dizziness. Causes eye irritation.

**Inhalation:** May cause drowsiness or dizziness.

**Skin Contact:** Causes skin irritation. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Eye Contact:** Causes eye irritation. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** Not available

### **Indication of Any Immediate Medical Attention and Special Treatment Needed**

If you feel unwell, seek medical advice (show the label where possible).

## SECTION 5: FIRE-FIGHTING MEASURES

### **Extinguishing Media**

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, dry chemical, or sand.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### **Special Hazards Arising From the Substance or Mixture**

**Fire Hazard:** Highly flammable liquid and vapor.

**Explosion Hazard:** May form flammable/explosive vapor-air mixture.

# HELMISOLV 667

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Reactivity:** Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.  
Reacts with (strong) oxidizers: (increased) risk of fire.

### **Advice for Firefighters**

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Do not allow run-off from firefighting to enter drains or water courses – may cause explosion hazard in drains and may reignite on surface water.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Decomposition may produce fumes, smoke, oxides of carbon and hydrocarbons. Oxides of Yttrium.

### **Reference to Other Sections**

Refer to section 9 for flammability properties.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment and Emergency Procedures**

**General Measures:** Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray). Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Use special care to avoid static electric charges. Keep away from heat, sparks, open flames, hot surfaces. – No smoking.

#### **For Non-Emergency Personnel**

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### **For Emergency Personnel**

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### **Environmental Precautions**

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### **Methods and Material for Containment and Cleaning Up**

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Do not take up in combustible material such as: saw dust or cellulosic material.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Use only non-sparking tools.

### **Reference to Other Sections**

See Section 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

## **SECTION 7: HANDLING AND STORAGE**

### **Precautions for Safe Handling**

**Additional Hazards When Processed:** Flammable vapors may accumulate in the head space of closed systems. Container may remain hazardous when empty. Handle empty containers with care because residual vapors are flammable. Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### **Conditions for Safe Storage, Including Any Incompatibilities**

**Technical Measures:** Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment. Use only non-sparking tools.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible Materials:** Strong oxidizers. Strong acids. Alkalis. Attacks some forms of plastics, rubber, and coatings.

### **Specific End Use(s)**

No use is specified.

# HELMISOLV 667

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

<b>Methyl acetate (79-20-9)</b>		
<b>Mexico</b>	OEL TWA (mg/m <sup>3</sup> )	610 mg/m <sup>3</sup>
<b>Mexico</b>	OEL TWA (ppm)	200 ppm
<b>Mexico</b>	OEL STEL (mg/m <sup>3</sup> )	760 mg/m <sup>3</sup>
<b>Mexico</b>	OEL STEL (ppm)	250 ppm
<b>USA ACGIH</b>	ACGIH TWA (ppm)	200 ppm
<b>USA ACGIH</b>	ACGIH STEL (ppm)	250 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	610 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	200 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	610 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	200 ppm
<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	760 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (STEL) (ppm)	250 ppm
<b>USA IDLH</b>	US IDLH (ppm)	3100 ppm (10% LEL)
<b>Alberta</b>	OEL STEL (mg/m <sup>3</sup> )	757 mg/m <sup>3</sup>
<b>Alberta</b>	OEL STEL (ppm)	250 ppm
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	606 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (ppm)	200 ppm
<b>British Columbia</b>	OEL STEL (ppm)	250 ppm
<b>British Columbia</b>	OEL TWA (ppm)	200 ppm
<b>Manitoba</b>	OEL STEL (ppm)	250 ppm
<b>Manitoba</b>	OEL TWA (ppm)	200 ppm
<b>New Brunswick</b>	OEL STEL (mg/m <sup>3</sup> )	757 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL STEL (ppm)	250 ppm
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	606 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (ppm)	200 ppm
<b>Newfoundland &amp; Labrador</b>	OEL STEL (ppm)	250 ppm
<b>Newfoundland &amp; Labrador</b>	OEL TWA (ppm)	200 ppm
<b>Nova Scotia</b>	OEL STEL (ppm)	250 ppm
<b>Nova Scotia</b>	OEL TWA (ppm)	200 ppm
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	760 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (ppm)	250 ppm
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	605 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (ppm)	200 ppm
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	760 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (ppm)	250 ppm
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	605 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (ppm)	200 ppm
<b>Ontario</b>	OEL STEL (ppm)	250 ppm
<b>Ontario</b>	OEL TWA (ppm)	200 ppm
<b>Prince Edward Island</b>	OEL STEL (ppm)	250 ppm
<b>Prince Edward Island</b>	OEL TWA (ppm)	200 ppm
<b>Québec</b>	VECD (mg/m <sup>3</sup> )	757 mg/m <sup>3</sup>
<b>Québec</b>	VECD (ppm)	250 ppm
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	606 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (ppm)	200 ppm

# HELMISOLV 667

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Saskatchewan</b>	OEL STEL (ppm)	250 ppm
<b>Saskatchewan</b>	OEL TWA (ppm)	200 ppm
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	760 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (ppm)	250 ppm
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	610 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (ppm)	200 ppm
<b>n-Heptane (142-82-5)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	400 ppm
<b>USA ACGIH</b>	ACGIH STEL (ppm)	500 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2000 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	500 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	85 ppm
<b>USA NIOSH</b>	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (ceiling) (ppm)	440 ppm
<b>USA IDLH</b>	US IDLH (ppm)	750 ppm
<b>Alberta</b>	OEL STEL (mg/m <sup>3</sup> )	2050 mg/m <sup>3</sup>
<b>Alberta</b>	OEL STEL (ppm)	500 ppm
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	1640 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (ppm)	400 ppm
<b>British Columbia</b>	OEL STEL (ppm)	500 ppm
<b>British Columbia</b>	OEL TWA (ppm)	400 ppm
<b>Manitoba</b>	OEL STEL (ppm)	500 ppm
<b>Manitoba</b>	OEL TWA (ppm)	400 ppm
<b>New Brunswick</b>	OEL STEL (mg/m <sup>3</sup> )	2050 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL STEL (ppm)	500 ppm
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	1640 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (ppm)	400 ppm
<b>Newfoundland &amp; Labrador</b>	OEL STEL (ppm)	500 ppm
<b>Newfoundland &amp; Labrador</b>	OEL TWA (ppm)	400 ppm
<b>Nova Scotia</b>	OEL STEL (ppm)	500 ppm
<b>Nova Scotia</b>	OEL TWA (ppm)	400 ppm
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	2049 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (ppm)	500 ppm
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	1640 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (ppm)	400 ppm
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	2049 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (ppm)	500 ppm
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	1640 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (ppm)	400 ppm
<b>Ontario</b>	OEL STEL (ppm)	500 ppm
<b>Ontario</b>	OEL TWA (ppm)	400 ppm
<b>Prince Edward Island</b>	OEL STEL (ppm)	500 ppm
<b>Prince Edward Island</b>	OEL TWA (ppm)	400 ppm
<b>Québec</b>	VECD (mg/m <sup>3</sup> )	2050 mg/m <sup>3</sup>
<b>Québec</b>	VECD (ppm)	500 ppm
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	1640 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (ppm)	400 ppm
<b>Saskatchewan</b>	OEL STEL (ppm)	500 ppm
<b>Saskatchewan</b>	OEL TWA (ppm)	400 ppm
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	2000 mg/m <sup>3</sup>

# HELMISOLV 667

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Yukon	OEL STEL (ppm)	500 ppm
Yukon	OEL TWA (mg/m <sup>3</sup> )	1600 mg/m <sup>3</sup>
Yukon	OEL TWA (ppm)	400 ppm

### Exposure Controls

**Appropriate Engineering Controls:** Gas detectors should be used when flammable gases/vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits. Use explosion-proof equipment. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

**Environmental Exposure Controls:** Do not allow the product to be released into the environment.

**Consumer Exposure Controls:** Do not eat, drink, or smoke during use

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear
Odor	: Ester
Odor Threshold	: Not available
pH	: Not applicable
Evaporation Rate	: 5.3, based on methyl acetate [ <i>Ref Std: n-Butyl acetate = 1.0</i> ]
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 132.8 – 136.4 °F (56 - 58 °C)
Flash Point	: 8.6 °F (-13 °C)
Auto-ignition Temperature	: >500 °C (932 °F)
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: 3.1 %
Upper Flammable Limit	: 16.0 %
Vapor Pressure	: <=171 mm Hg @ 20 °C (68 °F)
Relative Vapor Density at 20 °C	: >= 2.0 [ <i>Ref Std: Air = 1.0</i> ]
Relative Density	: 0.92 g/mL
Specific Gravity	: 0.92 @ 20 °C (68 °F)
Solubility	: Not soluble in water
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not applicable
Solids Content	: 0% (completely volatile)
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Yes, in certain circumstances product can ignite due to static discharge.
VOC Content (SCAQMD Rule 1171)	: 46 g/L VOC
VHAP Content	: 0 lbs/lb solids

# HELMISOLV 667

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Reacts with (strong) oxidizers: (increased) risk of fire.

**Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Ignition sources. Air contact. Incompatible materials.

**Incompatible Materials:** Strong oxidizers. Strong acids. Alkalis. Attacks some forms of plastics, rubber, and coatings.

**Hazardous Decomposition Products:** Decomposition may produce fumes, smoke, oxides of carbon and hydrocarbons. Oxides of Yttrium.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Not classified

**Serious Eye Damage/Irritation:** Causes serious eye irritation.

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not available

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness.

**Aspiration Hazard:** Small amounts of this liquid drawn into the lungs from swallowing or vomiting may cause severe health effects.

**Symptoms/Injuries After Inhalation:** May cause drowsiness or dizziness.

**Symptoms/Injuries After Skin Contact:** Causes skin irritation. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Symptoms/Injuries After Eye Contact:** Causes eye irritation. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

#### Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

<b>Methyl acetate (79-20-9)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 5 g/kg
LC50 Inhalation Rat	16000 ppm/4h
<b>n-Heptane (142-82-5)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	3000 mg/kg
LC50 Inhalation Rat	103 g/m <sup>3</sup> (Exposure time: 4 h)

### SECTION 12: ECOLOGICAL INFORMATION

**Toxicity** No additional information available

<b>Methyl acetate (79-20-9)</b>	
LC50 Fish 1	295 - 348 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	1026.7 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	250 - 350 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
<b>n-Heptane (142-82-5)</b>	
LC50 Fish 1	375.0 mg/l (Exposure time: 96 h - Species: Cichlid fish)

#### Persistence and Degradability

#### Bioaccumulative Potential

# HELMISOLV 667

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Methyl acetate (79-20-9)</b>	
Log Pow	0.18
<b>n-Heptane (142-82-5)</b>	
Log Pow	4.66

**Mobility in Soil** Not available

### Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Sewage Disposal Recommendations:** This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

**Additional Information:** Handle empty containers with care because residual product is flammable.

## SECTION 14: TRANSPORT INFORMATION

### In Accordance with DOT

**Proper Shipping Name** : PAINT RELATED MATERIAL  
**Hazard Class** : 3  
**Identification Number** : UN1263  
**Label Codes** : 3  
**Packing Group** : II  
**Marine Pollutant** : Marine pollutant  
**ERG Number** : 138



### In Accordance with TDG

**Proper Shipping Name** : PAINT RELATED MATERIAL  
**Packing Group** : II  
**Hazard Class** : 3  
**Identification Number** : UN1263  
**Label Codes** : 3  
**Marine Pollutant (TDG)** : Marine pollutant



## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations

<b>SARA Section 311/312 Hazard Classes</b>	Immediate (acute) health hazard Fire hazard
<b>Methyl acetate (79-20-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>Heptane, branched, cyclic and linear (426260-76-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>n-Heptane (142-82-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

### US State Regulations

<b>Methyl acetate (79-20-9)</b>
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

# HELMISOLV 667

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### **n-Heptane (142-82-5)**

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### **Canadian Regulations**

#### **Methyl acetate (79-20-9)**

Listed on the Canadian DSL (Domestic Substances List)  
Listed on the Canadian IDL (Ingredient Disclosure List)  
IDL Concentration 1 %

#### **Heptane, branched, cyclic and linear (426260-76-6)**

Listed on the Canadian DSL (Domestic Substances List)

#### **n-Heptane (142-82-5)**

Listed on the Canadian DSL (Domestic Substances List)  
Listed on the Canadian IDL (Ingredient Disclosure List)  
IDL Concentration 1 %

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

## **SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION**

**Revision Date** : 06/23/2020

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### **GHS Full Text Phrases:**

H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed or enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS US 2012 & WHMIS 2